Ohio Department of Health

Private Water Systems Contractor Well Inspection Report
For Pump, Pitless Adapter, Distribution Components, and Continuous Disinfection

Company Name	Work-site Contractor(s)	ODH Registration #				
Company Name	Work-site Contractor(s)	ODIT Registration #				
Local Health District	System Owner Name					
Address of System (street number, street name, city, state, zip)						
PLEASE CHECK AND COMPLETE ALL THAT APPLY						
Work type: ☐ New Construction ☐ Replacement ☐ Alteration ☐ Sealing (in conjunction with construction)						
Work type: - New constitution - Replacement - Alteration - Gealing (in conjunction with constitution)						
Pitless Adaptor / Pitless Unit	Casing Extension (cont.)	Additional service connections (cont.)				
Manufacturer:	Thickness: in.	☐ Yard Hydrants				
Model #:	Casing Extension Material	Installed: ☐ Yes ☐ No				
	☐ Thermoplastic ☐ PVC ☐ ABS	Number installed:				
☐ Conforms to Water Systems Council PAS- 97(4) Standard	SDR □ 13.5 □ 17 □ 21	Type: ☐ Sanitary meeting ASSE 1057				
97(4) Standard	□ SCH 40 PSI	☐ Frost-free				
☐ Pitless Adapter	☐ ASTM F-480 designation	☐ Backflow Prevention Devices				
Style: ☐ Clear-way ☐ Pull-Through	☐ Steel	Backflow device(s) installed for service connections?				
Other:	□ .188 □ .250 □ .375	☐ Yes ☐ No				
Method of cutting hole: ☐ Hole saw	□ other: in.	Number installed:				
☐ Cutting Torch	Method of attaching the extension:	Type of backflow prevention device				
□ w/ cutting guide	☐ Compression coupling device	installed ☐ ASSE 1024				
Depth below grade: ft / in ☐ Below frost-line	Manufacturer:	☐ ASSE 1013				
Method attached to casing:	Model number:	☐ Other:				
☐ Welded ☐ Bolted ☐ Clamped	☐ Steel Welded # of passes:	Well Cap				
Grout placed to bottom of pitless adapter?	□ Butt joint weld □ Collar □ Flare	Brand:				
☐ Yes ☐ No	☐ Threaded and coupled	Weather-tight: □Yes □No				
☐ Pitless Unit	☐ Solvent Weld/Glue (Glue)	Vermin Proof: □Yes □No				
Method attached to casing:	☐ Coupler ☐ Flare	Vented: □Yes □No				
☐ Threaded ☐ Welded ☐ Solvent Weld	Water service pipe distribution					
☐ Rubber expansion sealer	(refer to OAC 3701-28-08 Table 1 and 2)	Pressure Tank Number installed:				
☐ Bolted flanges with rubber gaskets	Pipe material (outside foundation):	Location(s):				
☐ Extends a min. of 12 inches above						
grade		☐ NSF 61 Approved				
Pump	ASTM designation:	☐ Buried ☐ Manufacturer documentation approving burial				
Manufacturer:	Pipe material (inside foundation):	☐ Pressure Relief Valve Installed				
Model #:		Sample faucet				
Type: ☐ Submersible ☐ Jet ☐ Hand Pump	ASTM designation:	☐ Accessible as per OAC 3701-28-08				
☐ Other:	☐ Additional service connections	Location:				
Source of Power:	Pipe material:	☐ at Pressure Tank				
☐ Electric ☐ Gas ☐ Pressurized Air	ASTM designation:	☐ Well side of Pressure Tank				
Other:	# of service connections:	☐ Extended to an accessible location ☐ after Continuous Disinfection System				
Pump depth set at: feet	Servicing: Dwelling, #	Other:				
Casing Extension	□ Building, #	Reason:				
Type of Casing Attaching to: ☐ Thermoplastic ☐ Steel	☐ Business	☐ Down-turned at least 45 degrees				
☐ Fiberglass	☐ Barn/Pole barn ☐ Other:	□ 8 in. or more above floor or ground□ Smooth-nosed (non-threaded)				
Nominal size: in.	☐ Yard Hydrant	_ cssassa (non anodaca)				

Ohio Department of Health

Private Water Systems Contractor Well Inspection Report
For Pump, Pitless Adapter, Distribution Components, and Continuous Disinfection

PLEASE CHECK AND COMPLETE ALL THAT APPLY

PLEASE GILLON AIND COMPLETE ALE THAT AFFET						
Continuous Disinfec	tion: Chlorine I	odine □Ozone □Ultraviole	et (UV)			
Chlorine and lodine		Ozone		Ultraviolet (UV)		
Chemical feed pump		☐ Corona Arc		☐ meets NSF standard 55 Class A		
Brand:		☐ Venturi		☐ Automatic shut-off		
		☐ Bubble diffuser		☐ Warning device		
Model #:		Retention tank size:	gallons			
Retention tank size:	gallons	☐ Ozone destruction		☐ Pre-treatment device installed prior to UV		
Baffled: □Yes	_	☐ Venting		☐ Cyst Reduction filter		
		Ozone residual:	ma/l	Brand:		
	ıl: mg/l	CT value:	_ 3	Number of filters:		
Calculated Retent	ion Time: min.			Absolute micron filter size: microns		
CT Value:		☐ Chemical resistant comp	onenis	☐ meets NSF 53 standard		
				☐ Flow rate: gal/min		
				☐ Labeled w/ absolute micron size		
				☐ Installed prior to UV		
Ponds, Springs, Cisterns Reason for installation Disinfection retenti Supplemental wate Low yield well rese Tank Location Basement Outside the fou Dimensions:x Volume: Material Concrete	s, and Hauled Water Storage ion er storage ervoir tank andation X gallons M specifications C 913 perglass		urface aning e depth to prevent utside foundation) th, free of rocks ge stones or debris	Manhole		
Additional Comment				bottom of tank		
PWS Contractor: Keep this record to demonstrate compliance with OAC 3701-28-04(F) and submit a copy with your Registration Application.						
Inspection Date	Inspecting Sanitarian's Signature		PWS Contractor's Signature			
Inspection Date	Inspecting Sanitarian's Signature		PWS Contractor's Signature			

^{*}The completed Inspection Report shall be distributed to the Private Water Systems Contractor, Local Health District, and the Ohio Department of Health.